

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



PATENT APPLICATION

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the Application of:

Brian George HOLLAND

Group Art Unit: Not Assigned

Application No.: Not Assigned

Examiner: Not Assigned

Filed: April 15, 2004

Attorney Dkt. No.: 108347-00022

For: DIGITAL TELEVISION DISPLAY CONTROL APPARATUS AND METHOD

CLAIM FOR PRIORITY

Director of the U.S. PTO
P.O. Box 1450
Alexandria, VA 22313-1450

Date: April 15, 2004

Sir:


The benefit of the filing date(s) of the following prior foreign application(s) in the following foreign country is hereby requested for the above-identified patent application and the priority provided in 35 U.S.C. §119 is hereby claimed:

In support of this claim, certified copy of said original foreign application is filed herewith.

It is requested that the file of this application be marked to indicate that the requirements of 35 U.S.C. §119 have been fulfilled and that the Patent and Trademark Office kindly acknowledge receipt of these/this document.

Please charge any fee deficiency or credit any overpayment with respect to this paper to Deposit Account No. 01-2300 referencing attorney docket number 108347-00022.

Respectfully submitted,



Eric B. Cherdak
Registration No. 39,936

4/15/04

Customer No. 004372
ARENT FOX PLLC
1050 Connecticut Avenue, N.W.,
Suite 400
Washington, D.C. 20036-5339
Tel: (202) 857-6000
Fax: (202) 638-4810
EBC:jns

THIS PAGE BLANK (USPTO)



INVESTOR IN PEOPLE


The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.


Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated 11 February 2004

THIS PAGE BLANK (USPTO)



1/77
30APR03 E803683-1 D01063
P01/7700 0.00-0309810.0

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
South Wales
NP9 1RH

1. Your reference RL.P52599GB
2. Patent application number 30 APR 2003
(The Patent Office will fill in this part) 0309810.0
3. Full name, address and postcode of the or of each applicant (underline all surnames)

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

Zarlink Semiconductor Limited
Cheney Manor
Swindon
Wiltshire
SN2 2QW
8177974001
United Kingdom
4. Title of the invention Digital Television Display Control Apparatus and Method
5. Name of your agent (if you have one) Marks & Clerk

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

4220 Nash Court
Oxford Business Park South
Oxford OX4 2RU
United Kingdom


7271125001

Patents ADP number (if you know it)
6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country	Priority application number (if you know it)	Date of filing (day / month / year)
---------	--	-------------------------------------
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application	Date of filing (day / month / year)
-------------------------------	-------------------------------------
8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:
a) any applicant named in part 3 is not an inventor, or
b) there is an inventor who is not named as an applicant, or
c) any named applicant is a corporate body.
See note (d))

Yes



The Patent Office

30APR03 E803683-1 D01063
P01/7700 0.00-0309810.0

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

Cardiff Road
Newport
South Wales
NP9 1RH

1. Your reference

RL.P52599GB

2. Patent application number

(The Patent Office will fill in this part)

0309810.0

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Zarlink Semiconductor Limited
Cheney Manor
Swindon
Wiltshire
SN2 2QW

Patents ADP number (if you know it)

8177974001

If the applicant is a corporate body, give the country/state of its incorporation

United Kingdom

4. Title of the invention

Digital Television Display Control Apparatus and Method

5. Name of your agent (if you have one)

Marks & Clerk

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

4220 Nash Court
Oxford Business Park South
Oxford OX4 2RU
United Kingdom

Patents ADP number (if you know it)

7271125001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country
Priority application number
Date of filing (if you know it)
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application
Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

Yes

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body.

See note (d))

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form
Description
Claim(s)
Abstract
Drawing(s)

13
3
1
2

22
8

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature Marks & Clerk Date

Marks & Clerk

29 April 2003

12. Name and daytime telephone number of person to contact in the United Kingdom

Dr. Robert Lind
01865-397900

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.


Patents Form 7/77

Patents Act 1977
(Rule 15)

The
Patent
Office

7/77

Statement of inventorship and of
right to grant of a patent



The Patent Office

Cardiff Road
Newport
South Wales
NP9 1RH

1. Your reference

RL.P52599GB

2. Patent application number
(if you know it)

0309810.0

30 APR 2003

3. Full name of the or of each applicant

Zarlink Semiconductor Limited

4. Title of the invention

Digital Television Display Control Apparatus and Method

5. State how the applicant(s) derived the right
from the inventor(s) to be granted a patent

By virtue of employment

6. How many, if any, additional Patents Forms
7/77 are attached to this form?
(see note (c))

7.

I/We believe that the person(s) named over the page (and on
any extra copies of this form) is/are the inventor(s) of the invention
which the above patent application relates to.

Signature
Marks & Clerk

Robert Lind Date

29 April 2003

8. Name and daytime telephone number of
person to contact in the United Kingdom

Dr. Robert Lind
01865-397900

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there are more than three inventors, please write the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form.
- d) When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant.
- e) Once you have filled in the form you must remember to sign and date it.

Patents Form 7/77

Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

Brian George HOLLAND
Westways
The Downs
Looe
Cornwall
PL13 2BD
UNITED KINGDOM

Patents ADP number (if you know it):

8022433001

Patents ADP number (if you know it):

Reminder

Have you signed the form?

Patents ADP number (if you know it):

Digital Television Display Control Apparatus and Method

The present invention relates to a method and apparatus for controlling a digital television display. More particularly, though not necessarily, the invention relates to the display of on-screen display graphics on a digital television display.

The display of a digital television signal is usually facilitated by means of a set-top box connected between the television signal receiver (e.g. aerial or satellite dish) and the television itself. Of course, the functionality of the set-top box may be incorporated into the television. Consumers have an expectation regarding the costs of set-top boxes. Typically, they expect them to be relatively cheap, for example in the region of £100. This expectation places severe restraints on set-top box design, particularly in terms of the processing power and memory which they can provide. In order to achieve such low cost products, manufacturers have sought to provide essentially single-chip solutions in which all of the processing required to decode and display the television signal is provided on a single chip. The only significant component not provided on this chip will be a main memory, typically an SDRAM.

Any competitive set-top box product must have a facility for displaying on-screen display (OSD) graphics. These appear on-screen as graphic elements overlaid on the video signal, and may for example be used to provide channel identifiers (e.g. BBC1, BBC2, etc) and volume level indicators. OSD graphics are stored as bitmap images in the main SDRAM. A bitmap comprises a colour code for each pixel to be displayed on the screen, at a position within a two dimensional storage array which reflects the actual screen resolution. The colour code can be in various formats, each requiring a different number of bits ranging, typically, from 4 to 32 bits. The formats encompass true, or direct, colour representations in which a number of bits are allocated to each colour component (RGB or luma/chroma), through to a colour code which represents a limited choice out of a range of colours defined by the originator. When the bitmap is to be displayed, this code is translated to a real colour through a lookup table stored in the SDRAM.

The SDRAM also provides two areas referred to here as OSD frame stores. Each OSD frame store is an area of memory mapped to the television display, i.e. each memory element of the frame store is mapped to a corresponding pixel of the display. The OSD graphics to be overlaid on a video frame are loaded into a frame store prior to display.

5 The frame store data is then read out, line by line, and passed to a mixer where it is mixed with the video data. Mixing may be done using a process known as "alpha blending" which allows image data to be layered, with underlying layers being visible to a greater or lesser extent. Whilst data is being read from one OSD frame store, the other OSD frame store is being loaded with the data for the next frame. Typically, the

10 SDRAM also provides a pair of video frame stores which are loaded with video data. Data is read from each of the video frame stores in turn, for mixing with the OSD data.

A typical OSD or graphics screen consists of a number of separate, but smaller, bitmaps ("objects") which are put together (or composed) at display time. With the frame store

15 approach these objects must be copied from their normal storage area into the correct position in the complete frame store. If an object is repeated, it has to be copied more than once, i.e. it has to be copied to several positions in the frame store. Every time an object moves (e.g. during an animation sequence) the complete frame store must be re-composed. The need to fill the background space between individual objects also

20 complicates the frame store composition process.

The copying of pixels belonging to an object is done using software running on the main processor of the set-top box. This is a time consuming process, wasting much of the power of the main processor and the available access bandwidth in the common

25 storage area (i.e. the maximum rate at which data can be written to and read from the SDRAM). The software copying of a pixel is known as a BitBlt operation, and is sometimes assisted by a special hardware BitBlt Processor. However, this does not reduce the storage bandwidth requirements.

30 With the frame store approach, the whole contents of the OSD frame store is read out at the screen display rate. This represents an extremely inefficient use of processing power and of the memory bandwidth, given that the OSD or graphic to be displayed

often occupies only a small area of the screen (or several small areas of the screen), with video occupying the rest of the screen.

5 In order to reduce the processing and memory bandwidth requirements, hardware in present generation Digital TV Systems uses the concept of planes (usually four) and regions in order to construct a user screen. Planes allow backgrounds, still video, and OSD to be overlaid with a fixed priority order, and then merged with the decoded video. Regions are bitmap areas in the OSD plane, which are usually smaller than the display screen but which have the same pixel resolution and use a common colour lookup table. 10 Unfortunately, hardware restrictions prevent regions from occupying the same TV line, never mind actually overlapping with a specified display priority.

The provision of hardware to implement planes and regions does to some extent reduce the software burden in constructing a screen. This is because only a region which is 15 smaller than the full screen may have to be composed from the various bitmap images (or objects) which make up the OSD plane. The process, however, still involves physically moving bitmaps around in the SDRAM in order to construct a single bitmap for the complete region. Every time an object is moved, the whole process still has to be repeated.

20

Provider specifications now require that video stills be repeated over the screen (tiling effects), and that vertical wipes between stills be possible. They also ask for animation in the OSD plane, and require that Digital Video Broadcasting (DVB) subtitling requirements be supported. The DVB specification for subtitles defines the concept of 25 objects and regions, where a region can contain many objects with no restrictions on line occupancy. A region is simply a vertically separated area on the screen with a common colour palette and background fill colour. The descriptors for objects allow them to be characters or bitmaps, and give each object an identification number (ID). The region descriptor defines which objects are to be present through their ID numbers, 30 and also defines the position of each object on the screen. Thus objects can be repeated in the region without the need to transmit the bitmap of that object more than once.

Unfortunately present generation systems would have to construct each region as a complete bitmap in their microprocessor memory space. Thus each received object bitmap would have to be moved from its own storage area into the correct physical position in the memory representation of a complete region. In addition, the vacant
5 space between objects within a region would have to be filled with a defined colour. When an object is moved or deleted the whole region would have to be re-constructed.

It is an object of the present invention to reduce the need for extensive BitBIT operations, and also to eliminate the need to read the contents of a complete OSD frame
10 store when the OSD or graphic area(s) is(are) smaller than full screen.

According to a first aspect of the present invention there is provided apparatus for controlling a digital television display, the apparatus comprising:

- a main processor;
- 15 a main memory coupled to said main processor via address and data busses, the main memory being arranged to store at least temporarily video data for display, and on-screen display graphics for overlaying on video data;
- mixing means for mixing video data read from the main memory under the control of the main processor, with on-screen display graphic data;
- 20 at least one line buffer for storing a line of on-screen display graphic data; and
- hardware processing means for composing a line of on-screen display graphic data in the line buffer by reading appropriate on-screen display graphic data from said main memory and writing it to the line buffer, and for providing the composed line of data to said mixing means.

25 Typically, the line buffer is a random access memory, having input/output data and address lines.

As the line buffer is not a part of the main memory, only a single main memory read
30 operation is required per on-screen display graphic/per line. It is not necessary to transfer graphic data between locations in the main memory. Read-out from the line buffer does not occupy the main memory access bandwidth or the main processor.

Therefore, whilst the line buffer is being written to and read from, the main processor can be performing other tasks, and the main memory accessed for other purposes.

Preferably, the apparatus comprises at least two line buffers, one of the buffers being
5 written to by said hardware processing means whilst the other is being read from.

Preferably, the apparatus comprises a first memory for storing a list of on-screen display objects and a second memory for storing object descriptors, each entry in said list pointing to an object descriptor, and each descriptor specifying a bitmap stored in said
10 main memory. The main processor is arranged to load into the first and second memories, for each frame to be displayed, object and descriptor data for that frame. Based upon the contents of the first and second memories, said hardware processing means reads appropriate on-screen display graphic data from said main memory and writes it to the line buffer.

15 Preferably, said main processor, said line buffer(s), and said hardware processing means are integrated onto a single chip, with the main memory being provided on a separate device.

20 According to a second aspect of the present invention there is provided a method of controlling a digital television display, the method comprising:

in a main memory controlled by a main processor, storing at least temporarily video data for display, and on-screen display graphics for overlaying on video data;

composing a line of on-screen display graphic data in a line buffer by reading
25 appropriate on-screen display graphic data from said main memory and writing it to the line buffer; and

reading data from the line buffer and mixing the read data with video data read from the main memory.

30 Preferably, said on-screen display graphics comprise one or more objects, each represented by a corresponding bitmap.

Preferably, the method comprises loading an object list into a first random access memory, the list defining objects to be displayed in a display frame, and loading a descriptor list into a second random access memory, the descriptor list defining bitmap characteristics and main memory storage locations. Entries in the object list point to entries in the descriptor list. For a given frame, the contents of the first and second memories are inspected to determine which on-screen display graphics data should be loaded into the line buffer, on a line-by-line basis. Preferably, this comprises comparing the vertical extent of each graphic or object with the vertical location of the line currently under construction in the line buffer. If the graphic contributes to the current line, the corresponding line data for the graphic is read from the main memory to the line buffer.

Preferably, where graphic data is stored in the main memory in RGB colour space, the data is converted to YcrCb colour space prior to writing it to the line buffer.

Preferably, where graphic data is stored in the main memory in 4:4:4 colour resolution, data read from the line buffer is converted into 4:2:2 colour resolution prior to mixing with video data.

For a better understanding of the present invention and in order to show how the same may be carried into effect, reference will now be made by way of example to the accompanying drawings, in which:

Figure 1 illustrates schematically the architecture of a set-top box for use in providing digital video signals to a television display; and

Figure 2 is a flow diagram illustrating a method of operation of the set-top box of Figure 1.

There is illustrated in Figure 1 an exemplary architecture for a set top box. The set top box receives at a video input 2 a digital television signal. This signal is passed to a decoder 3. Under the control of a main processor 4, the output signals from the decoder 3 are written to one of two areas of a main memory (SDRAM) 5 referred to here as the video "frame stores". These frame stores are mapped to the television display screen. Whilst data is being read out from one of the frame stores, data is being written to the

other. On-screen display (OSD) graphics or "objects" are also stored in the SDRAM 5 as bitmap images. These may be stored either with a 4:4:4 colour resolution or a 4:2:2 colour resolution, and either in RGB or YcrCb colour space.

5 The main processor 4 implements a decision to display OSD graphics. This process makes use of two dedicated memories, an object list RAM 6 and an object descriptor RAM 7, coupled to the processor bus. Typically, whilst the SDRAM 5 is provided by an off-chip memory device, the object list and object descriptor RAMs are integrated onto the same chip as the main processor 4 and other components shown within the box
10 8 in Figure 1. Read-out from the object list RAM 6 is controlled by a hardware controller 9, and is provided to an input of an object descriptor RAM 7 which is also controlled by the hardware controller 9. Outputs from the object descriptor RAM 7 are provided to an input of the hardware controller 9, which, in dependence upon the data provided at this input, controls read-out from the SDRAM 5.

15 Data read-out from the SDRAM 5 under the control of the hardware controller 9 is provided to an input of a colour table block 10. This block converts the colour data according to a colour coding specified by the hardware controller 9. The hardware controller 9 also provides control inputs to turn-on and off an RGB to YcrCb conversion
20 block 11 (as required). The output from the colour table block 10 (or optionally the RGB to YcrCb conversion block 10) is provided to an input of a multiplexer 12 which also receives at respective further inputs region colour and region fill data. The output from the multiplexer is applied to an input of one of a pair of line stores 13a, 13b implemented in standard on-chip static RAM. The line stores receive a control signal
25 from the hardware controller 9 which identifies, for a given line, the starting (x) position of an object on that line.

Outputs from the line stores 13a, 13b are provided to an input of a colour decimate block
30 14 which decimates 4:4:4 colour resolution bitmap images down to the 4:2:2 resolution required for video, if the bitmaps are not already stored in this format in the SDRAM 5. The output from the colour decimate block 14 is provided to one of two inputs of an alpha blender 15. The other input to the alpha blender is provided by an output of a video presentation controller 16 which reads (4:2:2, YcrCb) data out from one of the

two video frame stores at the appropriate rate. The output of the alpha blender 15 is provided to an input of a composite video encoder 17 which generates the signal for driving the display (converting colour components into composite video).

- 5 A video sync generator 18 provides a line count signal to the hardware controller 9, incremented at the line update rate of the display. The hardware controller 9 receives at a second input an output from the object descriptor RAM 7 specifying the start and end lines for a given object to be displayed. The hardware controller 9 makes a decision on whether an object contributes data to the current line as indicated by the line count
10 signal, and provides a read signal to the SDRAM 5 if the answer is yes.

The Object List and Descriptor RAMs 6,7 are loaded by software (running on the main processor), during the vertical blanking interval before a new frame is to be displayed, with object data for the next but one frame. The Descriptor RAM 7 is loaded with
15 information specifying each object which is to be displayed, namely:

- SDRAM memory start address of the object bitmap.
- A memory offset which allows only a window within an object to be displayed.
- The horizontal (X) position on the screen. The X position defines the first line
20 buffer write address, and objects can be moved by simply changing these co-ordinates.
- The width of the rectangle encompassing the part of the object which is to be displayed in pixels.
- The start and end lines of the object to be displayed, with reference to active graphics lines (1 - 480 for NTSC, or 1 - 576 for PAL).
- 25 • The pixel resolution in a specified format.
- The global video alpha blending value when pixel blending is not to be used.
- A bit to enable the above operation on an object by object basis.
- A bit to indicate overwriting of an existing pixel rather than blending with existing pixel.
- 30 • A bit to use Colour 0 as a transparency indicator.
- An identification field for the colour lookup table.

- A bit which indicates that the object is a DVB region fill (pseudo) object, with a single pixel value.

A typical bit allocation is given below, arranged around three, 32 bit words.

5

<u>Word 1</u>	Screen X position	10 bits
	Start Line	10 bits
	End Line	10 bits
	Region Fill enable	1 bit
10	Transparency on/off	1 bit

<u>Word 2</u>	Memory address	23bits
	CLUT address	6 bits
	Global alpha value	2 bits

15

<u>Word 3</u>	Pixel Format	4 bits
	Object width	10 bits
	Address Offset (for object window)	16 bits
	Object-alpha blending-on/off	1-bit

20

The List RAM 6 is loaded during the vertical blanking interval with a list of the objects which are to be displayed in the current frame, with the order defining the display priority if alpha blending is disabled (priority increasing with increasing position in the list). In effect, each object is defined by a pointer to the position of its descriptor words in the Descriptor RAM. Additional bits allow N objects to be skipped if they are not needed in a particular frame. Objects can thus be added, deleted, have their priority changed, or just skipped without changing the descriptor RAM until absolutely necessary, further reducing the load on the processor and use of the SDRAM bandwidth.

30

As already mentioned, two 720 x N bit line stores 13a,13b are provided, where N depends on the application. In a typical digital TV system the colour would be in the Y Cr Cb space, where 6 bits for Y plus 5 bits for each of the colour components would be

adequate. A 2 bit video alpha value is sufficient, and N is thus 18 bits. (An extra bit would allow OSD bitmaps to be in 4:4:4 or 4:2:2 spatial resolution.)

Once the object list and object descriptor RAMs 6,7 have been loaded, control of the
5 process is taken over by the hardware controller 9. Amalgamated bitmaps are
composed one line at a time using one of the line stores, whilst the previously composed
line buffered in the other line store is being read. This process is illustrated in the flow
diagram of Figure 2. After loading of the object list and object descriptor RAMs 6,7,
for each line, the hardware controller 9 cycles through all of the objects contained in the
10 list RAM 6, once per active horizontal video line. For each object, the object descriptor
RAM 7 passes the corresponding line position data to the hardware controller 9. If the
object does not contribute to the line under construction, the next object in the list is
read. If the read object does contribute to the line under construction, the appropriate
line of the corresponding bitmap is caused to be read from the SDRAM 5 and supplied
15 to the input of the colour table block 10.

The start address of the first line of an object is contained in the object descriptor, and
the address is incremented up to the width of the object. For each further line to be
displayed in the current screen, the start address is always the start SDRAM address
20 contained in the descriptor plus the object width in words contained in the descriptor
multiplied by the difference between the current line count and the start line.

Each SDRAM memory read operation returns a 32 bit word from the SDRAM 5. This
is parsed into individual pixels, depending upon the pixel resolution. Writing to the line
25 buffer 13a,13b is inhibited should the X address be greater than 720, although this
would only happen in the event of a software error. Bitmap data is written in the correct
X position in the line buffer 13a,13b (relative to the screen), and can either replace data
previously written in the corresponding locations, or can be alpha blended with previous
object data.

30

The construction process could be based on the use of a 10 bit line counter and a 10 bit
pixel counter, which between them define the XY position on the screen. The pixel
counter is used to address the line buffer and defines 720 pixel locations per line. The

line counter defines an active line in a complete video frame, i.e. 1 - 576 in PAL and 1 - 480 in NTSC.

5 The line counter is initialised to the value 001 hex at the start of the last blanked line before the top field is displayed. It then increments by two at some time during each horizontal flyback. At the start of the last blanked line before the bottom field is displayed, the line counter is initialised to the value 002 hex, and it then increments by two during each horizontal flyback. With this arrangement odd values of the line counter always indicate positions above even values, and the line count value is one
10 field line ahead of when an objects loaded into the line buffer will be displayed.

The display of an object can start in any field, but these objects are actually stored as consecutive lines within the SDRAM (i.e. not as two separate fields). The top left hand pixel is stored in the first SDRAM word assigned for that object. The pixels produced
15 from lesser significant bits will be displayed to the left of those from higher significant bits.

An automatic background fill facility is provided, and this is enabled with a control bit which is detected by the hardware controller 9. This loads the complete line buffer with
20 a background fill colour which has been previously defined by software. This is done during the horizontal flyback after the previous contents of the line buffer have been displayed, and results in the background fill requiring no external memory bandwidth or processing power. This background colour has the lowest display priority, and when applicable will be replaced by a DVB region fill or an object.

25 When alpha blending between OSD objects is not supported, the latest pixel from an overlapping object replaces the current line buffer contents. However, if the new pixel value is all zeros, a write to the line buffer at that pixel location is inhibited. Such an all zero value defines a hole in the object through which a previous object should still be
30 visible. Since objects are rarely rectangular in shape, then 'holes' will be necessary to fill in a complete rectangle.

In the system presented here, the DVB concept of regions is needed only to identify objects using the same colour lookup table. Thus software must use the DVB object_id, which identifies the objects within a particular region, to define a fixed CLUT address for all objects within the region. If the DVB region_fill_flag is set however, a special region object must be defined in the list of objects to be displayed. A region object indicator flag is provided for this purpose, and, when set, a single colour rectangular object will be loaded into the line buffer by the control block. No SDRAM fetches are required for this object and the resulting spare address bits can alternatively be used to define the pixel value, be it 4/8 bits per pixel or true colour. The remaining descriptor bits are used for their usual purpose, and define the CLUT and screen position of the DVB region. Several region objects can be defined, but they will not occupy the same lines if they are DVB compliant (although overlaps would not actually cause a problem). These region objects must have the lowest object display priority.

Bitmap objects can now be created anywhere in system memory (SDRAM), without any relationship to their physical position on the screen. There is no need to move them to a separate bitmap area defining a region or frame. By allowing random writes to the line buffer, but which correspond to the horizontal position on the screen, a line representing the amalgamation of all objects on that line can be composed just before display time. Only the lines of bitmap objects which are to be displayed on a particular line have to be fetched from the storage area. A complete OSD line only has to be fetched only if an OSD occupies the complete line.

Objects which overlap simply cause overwriting to occur at a line buffer addresses, and the order of writing the objects corresponds to the display priority. The amount of object overlapping in any one line is only limited by the increase in memory bandwidth required to fetch pixels from SDRAM which are never actually seen on the screen. Object overlapping does, however, require that one of the pixel values is actually transparent and inhibits a write to the line buffer at that location. In other words, when an object is written on top of another object, the new object may have holes in it which allow the original object still to be visible. One of the pixel values thus has to mean a 'hole' rather than a colour. When this pixel value is detected, the write to the line buffer is inhibited at that pixel position.

- Alternatively, alpha blending is possible between overlapping objects, rather than simply overwriting an object with a new object. A read modify write operation is then needed every time a pixel is written to the line buffer. Alpha blending is of course only
- 5 possible if the pixel colour format represents a true colour, rather than an index to a lookup table. The colour format must also contain bits which represent an alpha value for that pixel, or alternatively a common alpha value can be defined for the whole object.
- 10 The proposed system avoids the need for frame stores, planes and OSD regions. The line buffer can be loaded with a background colour during the horizontal flyback period such that this operation does not require any bandwidth from the storage area, and thus background filling between objects is obtained for 'free'. Only pixels for the actual objects need be fetched from the SDRAM.
- 15 It will be appreciated by the person of skill in the art that various modifications may be made to the above described embodiment without departing from the scope of the present invention.
-

CLAIMS:

1. Apparatus for controlling a digital television display, the apparatus comprising:
 - a main processor;
 - a main memory coupled to said main processor via address and data busses, the main memory being arranged to store at least temporarily video data for display, and on-screen display graphics for overlaying on video data;
 - mixing means for mixing video data read from the main memory under the control of the main processor, with on-screen display graphic data;
 - at least one line buffer for storing a line of on-screen display graphic data; and
 - hardware processing means for composing a line of on-screen display graphic data in the line buffer by reading appropriate on-screen display graphic data from said main memory and writing it to the line buffer, and for providing the composed line of data to said mixing means.
2. Apparatus according to claim 1, the apparatus comprising at least two line buffers, one of the buffers being written to by said hardware processing means whilst the other is being read from.
3. Apparatus according to claim 1 or 2 and comprising a first memory for storing a list of on-screen display objects and a second memory for storing object descriptors, each entry in said list pointing to an object descriptor, and each descriptor specifying a bitmap stored in said main memory.
4. Apparatus according to claim 3, the main processor being arranged to load into the first and second memories, for each frame to be displayed, object and descriptor data for that frame, and, based upon the contents of the first and second memories, said hardware processing means is arranged to read appropriate on-screen display graphic data from said main memory and writes it to the line buffer.
5. Apparatus according to claim 4, said hardware processing means being arranged to load background fill colour data into locations of the line buffer in dependence upon descriptor data contained in said second memory.

6. Apparatus according to any one of the preceding claims, wherein said main processor, said line buffer(s), and said hardware processing means are integrated onto a single chip, with the main memory being provided on a separate device.
7. A method of controlling a digital television display, the method comprising:
 - in a main memory controlled by a main processor, storing at least temporarily video data for display, and on-screen display graphics for overlaying on video data;
 - composing a line of on-screen display graphic data in a line buffer by reading appropriate on-screen display graphic data from said main memory and writing it to the line buffer; and
 - reading data from the line buffer and mixing the read data with video data read from the main memory.
8. A method according to claim 7, wherein said on-screen display graphics comprise one or more objects, each represented by a corresponding bitmap.
9. A method according to claim 7 or 8 and comprising loading an object list into a first random access memory, the list defining objects to be displayed in a display frame, and loading a descriptor list into a second random access memory, the descriptor list defining bitmap characteristics and main memory storage locations, where entries in the object list point to entries in the descriptor list.
10. A method according to claim 9, wherein, for a given frame, the contents of the first and second memories are inspected to determine which on-screen display graphics data should be loaded into the line buffer, on a line-by-line basis.
11. A method according to claim 10, comprising comparing the vertical extent of each graphic or object with the vertical location of the line currently under construction in the line buffer, and, if the graphic contributes to the current line, the corresponding line data for the graphic is read from the main memory to the line buffer.
12. A method according to any one of claims 7 to 11, where graphic data is stored in the main memory in RGB colour space, the data being converted to YcrCb colour space prior to writing it to the line buffer.

13. A method according to any one of claims 7 to 12, where graphic data is stored in the main memory in 4:4:4 colour resolution, and data read from the line buffer is converted into 4:2:2 colour resolution prior to mixing with video data.

ABSTRACT

Digital Television Display Control Apparatus and Method

Apparatus for controlling a digital television display, the apparatus comprising a main processor 4, a main memory 5 coupled to said main processor 4 via address and data busses, the main memory 5 being arranged to store at least temporarily video data for display, and on-screen display graphics for overlaying on video data. Mixing means 15 is provided for mixing video data read from the main memory 5 under the control of the main processor 4, with on-screen display graphic data. At least one line buffer 13a,13b is provided for storing a line of on-screen display graphic data. Hardware processing means 9 is arranged to compose a line of on-screen display graphic data in the line buffer 13a,13b by reading appropriate on-screen display graphic data from said main memory 5 and writing it to the line buffer, and for providing the composed line of data to said mixing means 15.

Figure 1




Figure 1

THIS PAGE BLANK (USPTO)




Figure 2

THIS PAGE BLANK (USPTO)